

### TC-600 Solar Power

- Operates 24/7 with solar power supply
- Power Supply: Two 12-volt, 18 amp/hour AGM batteries (UL recognized) | Provides up to 14 days of back-up operation on fully charged batteries
- Power consumption: < 2.0 amps (24w) at maximum display intensity
- Idle mode: < 1/2 watt
- Circuit breaker: Multi-circuit | 3 x 10 amp fuses
- Battery status: Check battery charge levels and solar amperage via Wi-Fi
- Low battery cut-off feature provides intelligent battery management
- Solar panel output: 50 watt standard
- Solar charger: Fully integrated charge controller with continuous monitoring and data logging of solar output/ battery charge status
- Charger and battery characteristics matched to operate within the sign's operating temperature range

### LED Display

- 13" tall speed display numbers | 2 or 3 digit capable
- Speed digits easily readable up to 600 feet
- Ideal for roads with traffic speeds of 5-70 mph
- Super bright amber LEDs in full matrix design | Life up to 100,000 hours
- Laser cut flat black mask enhances visibility of LED display when illuminated | Ensures completely dark display when LEDs are off
- Display brightness fully automatic or user adjustable

### Speed Violator Alerts

- Standard alerts: SPEED (3 flash rate options) | Enhanced font | SLOW DOWN | TOO FAST
- Speed display flash rates: MUTCD flash (approx. 55-60 fpm) | slow flash (approx. 90 fpm) | fast flash (approx. 140 fpm)
- *Optional* message alerts: SHARP CURVE | Right or left facing chevrons | SCHOOL ZONE | FINE \$\$\$ | Smiley face | Custom message alert upon request
- Display speed and word message alerts, alternately or individually, based on speed settings
- *Optional* strobe alerts - *Choice of one*: alternating red/blue strobe alert or white strobe alert (can simulate a camera flash)

### YOUR SPEED Faceplate

- 28"W x 33"H YOUR SPEED faceplate with 4" high lettering
- *Optional* oversized 30"W x 36"H YOUR SPEED faceplate available
- Manufactured with highest grade reflectivity backing
- Available in white | yellow | fluorescent yellow/green | safety orange

### Radar

- Type: K Band, single direction Doppler radar | FCC part 15 compliant | No license required
- Sensor Range: Detects vehicles up to 1200 feet
- Beam Width: 12 degrees, +/- 2 degrees
- Operating Frequency: 24.125 GHz, +/- 50 MHz
- Accuracy: +/- 1.0 mph
- Speed Detection Range: 5-127 mph | 8-198 kph

### TC-600 AC Power

- Operates 24/7 with AC power supply
- Power supply: Hard wire to 100V-240V power supply
- Power consumption: < 2.0 amp (24w) at maximum display intensity
- Idle mode: < 1/2 watt
- Circuit breaker: Multi-circuit, 10 amp fuse



Certified Quality System  
ISO 9001:2015



MUTCD Compliant  
Radar Speed Signs



Proudly Engineered &  
Manufactured in the USA



### **Electronics**

- All power inputs are fused and reverse polarity protected
- All circuit boards are conformally coated for extra protection
- Sign has automatic reset and watch-dog circuitry to return to normal operation without user intervention

### **Radar Speed Sign Housing**

- Dimensions: 18.5"H x 26.25" W x 5.0"D
- Thickness: .1875" to .25" thick, heavy-duty aluminum
- IP65 compliant | NEMA 4 level compliant
- Humidity Maximum: 100% | Non-sealed and ventilated
- Provides maximum protection from the elements and vandalism
- Single-piece cast aluminum housing design | Seamless construction with no welding
- Stainless steel mounting hardware included for poles up to 4.5" OD

### **Weights & Operating Temperature**

- TC-600 solar power radar speed sign: 61 lbs.
- TC-600 AC power radar speed sign: 35 lbs.
- Operating temperature: -40°F to +160°F

## **Standard Features on All Radarsign Brand Models**

### **Bashplate™ with Integrated LED Reflector Cones**

- Heavy duty aluminum shield over LED display to protect components from abuse or vandalism
- Directional beam technology, Radarsign's proprietary design, includes beveled cones around each LED, magnifying the intensity of the light and providing the highest quality viewable display with minimum energy usage

### **Polycarbonate Display Cover**

- .25" thick protective sheet covers entire display area
- Abrasion, graffiti and shatter resistant | Provides UV protection

### **Wi-Fi Enabled**

- Radar speed sign emits it's own Wi-Fi signal | No internet required | Manage sign with smart phone, tablet, or laptop
- Connection range up to 300 feet from sign
- Allows for quick and easy sign operation and data download from most web enabled devices
- Speed is 10x faster and has 10x the range of Bluetooth
- WPA2 encrypted security | Password protected
- OTA software updates (over-the-air) allow the wireless delivery of software updates and upgrades directly to the radar sign

### **Standard Programming**

- Setup functions: Easy to follow digital menu | No mechanical switches to operate
- Daily timers: Allow 5 on/off timer settings per day (4 timers plus the standard setting), also by day of week | Settings allow for lower speed limits for school zone times
- Stealth mode: Display on/off feature allows traffic data collection to continue even when the display is off
- Possum Switch™: Feature allows the sign to "play dead" for 30 minutes if attacked with force
- Maximum speed cutoff: Feature prevents "racing" of sign at high speeds | Choice of flashing dashes or LED display cutoff

### **Warranty**

- 2 year warranty on parts and labor, including batteries | *Exceptions:* Does not cover malicious abuse, theft, or damage due to unauthorized modification | *Optional* third year warranty extension available

## **Optional Scheduling and Data Reporting Features**

### **Advanced Scheduler**

Date driven program allows pre-programming multiple years and multiple schedules for your radar speed signs | Especially useful for school zone scheduling or in areas where events occur on a regular basis

### **Streetsmart Traffic Data Collection & Reporting Software**

*Lifetime license - One time charge - No recurring fees* | *Licensed per sign* - Download, report, organize, and analyze speed and traffic data that is recorded by the radar speed sign | Generate 35 charts and graphs with Excel™ macro | Traffic Data Storage Capacity: Stores data on 5 million vehicles | Retains data for 12 months in sign before writing over oldest data first

### **Cloud Service**

Cellular modem is cloud accessible from anywhere internet is available. Allows remote management of sign settings for entire network of signs | Uploads daily traffic statistics to Radarsign Cloud server (*requires the purchase of Streetsmart data license*) | Provides alerts if batteries run low, or connection is interrupted